SPECIFICATIONS

Effective Sept. 2, 2002

Supercedes April 1, 2001

1830 Centennial Ave.
Hastings, NE 68901
Ph: 402-462-2227
Fax: 402-462-5529
Toll Free: 866-851-2227
centennialplastics.com

Centennial PLASTICS LLC

CenFlo HDPE

HDPE 3408—ASTM D2239 and ASTM D2737 CTS

- Flexible polyethylene pipe and tubing
- Produced from only the finest virgin material
- Backed by a **30-YEAR WARRANTY**
- Virgin Black material

ASTM D2239			1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
80 PSI	SIDR 19	O.D.	N/A	N/A	1.169"	1.526"	1.810"	2.285"
		I.D.	N/A	N/A	1.049"	1.380"	1.610"	2.067"
		Wall	N/A	N/A	.060"	.073"	.100"	.109"
		Wt/ft	N/A	N/A	.093#	.148#	.231#	.324#
		Coil Lengths	N/A	N/A	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.
100 PSI	SIDR 15	O.D.	N/A	.944"	1.189"	1.564"	1.824"	2.343"
		I.D.	N/A	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	N/A	.060"	.070"	.092"	.107"	.138"
		Wt/Ft	N/A	.074#	.109#	.187#	.251#	.416#
		Coil Lengths	N/A	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.
125 PSI*	SIDR 11.5	O.D.	.742"	.968"	1.231"	1.620"	1.890"	2.427"
		I.D.	.622"	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	.060"	.072"	.091"	.120"	.140"	.180"
		Wt/Ft	.057#	.090#	.143#	.246#	.330#	.544#
		Coil Lengths	100-400 ft.	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.
160 PSI*	SIDR 9	O.D.	.760"	1.008"	1.283"	1.686"	1.968"	2.527"
		I.D.	.622"	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	.069"	.092"	.117"	.153"	.179"	.230"
		Wt/Ft	.066#	.116#	.186#	.320#	.430#	.710#
		Coil Lengths	100-400 ft.	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.
200 PSI*	SIDR 7	O.D.	.800"	1.060"	1.349"	1.774"	2.070"	2.657"
		I.D.	.622"	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	.089"	.118"	.150"	.197"	.230"	.295"
		Wt/Ft	.087#	.152#	.246#	.424#	.578#	.952#
		Coil Lengths	100-400 ft.	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

ASTM D2737 CTS			1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
200 PSI*	SDR 9	O.D.	N/A	.875"	1.125"	1.375"	1.625"	2.125"
		I.D.	N/A	.681"	.875"	1.069"	1.263"	1.653"
		Wall	N/A	.097"	.125"	.153"	.181"	.236"
		Wt/Ft	N/A	.103#	.170#	.254#	.353#	.602#
		Coil Lengths	N/A	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

*CenFlo 3408 SIDR 7, 9 & 11.5 pipe meets the requirements of AWWA C901.
*CenFlo 3408 CTS SDR9 pipe meets the requirements of AWWA C901.
Note: CenFlo HDPE SIDR 19, SIDR 15, SIDR 11.5, SIDR 9 and SIDR 7 are suitable for connections with insert fittings and clamps.
Note: CenFlo HDPE SDR 9 is suitable for connections with CTS compression fittings.

NSF CenFlo HDPE is tested and certified by NSF