

Product Description and Print Line

CenFlo HDPE 4710 Polyethylene Pipe

Material:

All CenFlo HDPE 4710 pipe is manufactured from virgin high density polyethylene resin with the cell classification of 445576C per ASTM D 3350. The material contains a minimum of 2% Carbon Black as a UV inhibitor to accommodate outside storage.

Print Line:

All CenFlo HDPE 4710 is permanently indent printed with white print stating the following:

- 1. Identification of Centennial Plastics as the manufacturer.
- 2. The appropriate SDR, SIDR and/or CTS designation and nominal diameter.
- Product trade name.
- 4. All relevant ASTM standards to which CenFlo is manufactured.
- Relevant NSF and AWWA standards.
- 6. Manufacturing dates using the Julian calendar.
- 7. Incremental footage marking every two feet.
- 8. Design temperature rating.
- 9. Production shift designation.
- 10. Identification of PE 4710 high density resin.

Recommended Usage:

CenFlo HDPE 4710 is recommended for use as the piping material for all potable water mains and service lines.

Connections:

CenFlo HDPE 4710 is manufactured to accommodate insert fittings and/or CTS compression fittings.

Handling:

Any handling of the pipe shall avoid contact with sharp edged objects. If stored outside for long periods of time, the pipe should be covered with a UV resistant tarp or cover. If the wall of the pipe is penetrated by more than 10% of its thickness, the damaged pipe should be cut out, disposed of and replaced.

Centennial Plastics is an ISO 9001 certified company.

CENTENNIAL PLASTICS, INC.